

60 AMP - Cast Aluminum

Receptacles, Plugs, Connectors, Motor Plugs

NEMA 4 Watertight
600 VAC / 250 VDC
50 - 400 Hz



DESCRIPTION AND CONFIGURATION		RECEPTACLE* W/ SPRING DOOR CAT. NO.	PLUG		CORD CONNECTOR		MOTOR PLUG CAT. NO.
			CABLE RANGE	CAT. NO.	CABLE RANGE	CAT. NO.	
2 Wire 3 Pole Style 2		AR632	0.50-1.45	APJ6385	0.50-1.45	APR6365	APQ638
3 Wire 3 Pole Style 1		AR631	0.50-1.45	APJ6375	0.50-1.45	APR6355	APQ637
3 Wire 4 Pole Style 2		AR642	0.50-1.45	APJ6485	0.50-1.45	APR6465	APQ648
4 Wire 4 Pole Style 1		AR641	0.50-1.45	APJ6475	0.50-1.45	APR6455	APQ647
4 Wire 5 Pole Style 2		AR658 ⁺	0.75-1.45	APJ6585	0.88-1.38 1.38-1.88	APR6565 APR6567	--
5 Wire 5 Pole Style 1		AR657 ⁺	0.50-1.45	APJ6575	--	--	--

*To order AR Receptacles complete with **screw cap** instead of spring door, change the last digit from 1 to 7 or 2 to 8; i.e., AR631 to AR637 **OR** AR642 to AR648 (see page 16 for screw caps).

⁺ Supplied with screw cap only.

- For optional reversed interior, use suffix "**S22**" (see page 3).
- For optional rotated interior, use suffix "**S4**" (see page 3).
- For dimensions, see page 15.
- Maximum conductor size (wire well) 0.312" (see page 17).

Back Boxes (for Receptacles and Motor Plugs) - See page 9